

RECESSED MULTI-HEAD GIMBAL

1, 2 & 3 HEAD
5 CCT SELECT



CCT SWITCH
ON THE BACK



1 HEAD
CCT CHANGE
2700K 3000K 3500K 4000K 5000K
12 WATT



2 HEAD
CCT CHANGE
2700K 3000K 3500K 4000K 5000K
24 WATT



3 HEAD
CCT CHANGE
2700K 3000K 3500K 4000K 5000K
36 WATT

COMPATIBLE WITH:	
LR35123 LR35124	
EM LED DRIVER	
LR41004	LR41007
NEW CONSTRUCTION MOUNTING PLATE	



SPECIFICATIONS

ELECTRICAL

	MODEL	DESCRIPTION	POWER	LUMEN	EFFICACY	INPUT VOLTS	DIMMABLE	FREQUENCY	LIFETIME	BEAM ANGLE
1 HEAD	LR32180	LEDMHDL1/5CCT/9/G	12	800	67	120V	YES	50/60Hz	50,000	40°
2 HEAD	LR32183	LEDMHDL2/5CCT/9/G	24	1400	58	120V	YES	50/60Hz	50,000	40°
3 HEAD	LR32185	LEDMHDL3/5CCT/9/G	36	2100	58	120V	YES	50/60Hz	50,000	40°

PHOTOMETRIC

MODEL	COLOR (CCT)	TEMP	CRI
LR32180	2700K/3000K/3500K/4000K/5000K	WARM/SOFT/NATURAL/COOL/BRIGHT	80
LR32183	2700K/3000K/3500K/4000K/5000K	WARM/SOFT/NATURAL/COOL/BRIGHT	80
LR32185	2700K/3000K/3500K/4000K/5000K	WARM/SOFT/NATURAL/COOL/BRIGHT	80

GENERAL

FINISH	WET LOCATION	IC RATED	ETL LISTED	ENERGY STAR
WHITE	YES	YES	YES	YES
WHITE	YES	YES	YES	YES
WHITE	YES	YES	YES	YES

DIMENSIONS

