

RECESSED MULTI-HEAD GIMBAL

1, 2 & 3 HEAD
5 CCT SELECT
BLACK FINISH



**CCT SWITCH
ON THE BACK**



1 HEAD



2 HEAD



3 HEAD



COMPATIBLE WITH:

**LR35123
LR35124**



EM LED DRIVER

LR41004

LR41007



NEW CONSTRUCTION MOUNTING PLATE



SPECIFICATIONS

ELECTRICAL

	MODEL	DESCRIPTION	POWER	LUMEN	EFFICACY	INPUT VOLTS	DIMMABLE	FREQUENCY	LIFETIME	BEAM ANGLE
1 HEAD	LR32181	LEDMHDL1/5CCT/9/G/BK	12	800	67	120V	YES	50/60Hz	50,000	40°
2 HEAD	LR32184	LEDMHDL2/5CCT/9/G/BK	24	1400	58	120V	YES	50/60Hz	50,000	40°
3 HEAD	LR32186	LEDMHDL3/5CCT/9/G/BK	36	2100	58	120V	YES	50/60Hz	50,000	40°

PHOTOMETRIC

MODEL	COLOR (CCT)	TEMP	CRI
LR32181	2700K/3000K/3500K/4000K/5000K	WARM/SOFT/NATURAL/COOL/BRIGHT	80
LR32184	2700K/3000K/3500K/4000K/5000K	WARM/SOFT/NATURAL/COOL/BRIGHT	80
LR32186	2700K/3000K/3500K/4000K/5000K	WARM/SOFT/NATURAL/COOL/BRIGHT	80

GENERAL

FINISH	WET LOCATION	IC RATED	AIRTIGHT	ETL LISTED
BLACK	YES	YES	YES	YES
BLACK	YES	YES	YES	YES
BLACK	YES	YES	YES	YES

DIMENSIONS

