


DIRECT/INDIRECT STEEL LINEAR



AVAILABLE MOUNTING STYLES



WALL MOUNT



ADJUSTABLE
AIRCRAFT



PENDANT
SWIVEL PENDANT

FEATURES

Direct/Indirect output linear. Wall or Suspended mounting - extended row mounting configurations available. Available in multiple standard lengths - Custom lengths available to match customer layouts. ADA compliant wall mounting under 4" depth. 0-10v dimming down to 1% standard (consult factory for other dimming options). **Construction:** heavy gauge cold rolled steel. **Finish:** standard polyester powder coat - white, black or silver standard colors - other finishes/colors available (consult factory). All components accessible from below for servicing. Fixtures cETLus listed for damp locations

ORDERING INFORMATION

FIXTURE TYPE:

PROJECT:

SERIES:

S35-DI

ORDER CODE:

1. SERIES

S33-DI

3. MOUNTING

W - WALL MOUNT
P - PENDANT/CANOPY (24" STANDARD)
SP - SWIVEL
PENDANT/CANOPY (24"/45" STANDARD)
AC - ADJUSTABLE AIRCRAFT
CABLE (48" STANDARD)

4. COLOR TEMP:

27K - 2700K
30K - 3000K
35K - 3500K
40K - 4000K
50K - 5000K*
30KS - 3000K BIOS® STATIC
35KS - 3500K BIOS® STATIC
40KS - 4000K BIOS® STATIC
30KD - 3000-2700K BIOS® DYNAMIC
35KD - 3500-3000K BIOS® DYNAMIC
40KD - 4000-3500K BIOS® DYNAMIC

*NOT AVAILABLE IN 90CRI

5. LUMEN OUTPUT DIRECT

035 - 350LM/FT - 2.2W/FT
055 - 550LM/FT - 3.4W/FT
085 - 850LM/FT - 5.1W/FT
110 - 1100LM/FT - 6.8W/FT
165 - 1650LM/FT - 10.6W/FT
220 - 2200LM/FT - 14.3W/FT

6. LUMEN OUTPUT INDIRECT

035 - 350LM/FT - 2.2W/FT
055 - 550LM/FT - 3.4W/FT
085 - 850LM/FT - 5.1W/FT
110 - 1100LM/FT - 6.8W/FT
165 - 1650LM/FT - 10.6W/FT
220 - 2200LM/FT - 14.3W/FT

2. DISTRIBUTION:

DI - DIRECT/INDIRECT

7. LENGTH+

2'- 2 FOOT
3'- 3 FOOT
4'- 4 FOOT
5'- 5 FOOT
6'- 6 FOOT
7'- 7 FOOT
8'- 8 FOOT

8. DIFFUSER

WOA - WHITE OPAL ACRYLIC LENS
LXT - LUMEN XT HIGH PERFORMANCE POLYCARBONATE

9. FINISH

WHT - WHITE POWDER COAT
BLK - BLACK POWDER COAT
SLV - SILVER POWDER COAT
CA - CUSTOM COLORS (CONSULT FACTORY)

10. VOLTAGE

UNV - UNIVERSAL (120/277V)

11. OPTIONS

GLR - IN LINE FUSING
EM - EMERGENCY BATTERY BACKUP
90C - 90+ CRI (NOT AVAILABLE IN 5000K)

+ See following pages for more information about this option



BIOS Illuminated®

BIOS SkyBlue® lighting solutions contribute to satisfying Circadian Lighting Design Feature 54 under WELL Building Standard v1 and Feature L03 under the WELL Building Standard v2. BIOS SkyBlue also meets other features within the WELL Light Concept, including color quality with 83+ CRI and R9 values at 90, visual comfort metrics, and higher m/p ratios than traditional LED lighting.

STATIC LIGHT ENGINE - Option Codes 30KS, 35KS, 40KS

BIOS SkyBlue Static Spectrum lighting solutions support proper daytime circadian stimulus, communicating directly with human circadian biology through a non-visual photo receptor in the eye. With SkyBlue, there is no need for color tuning, color temperature adjustments or significantly increasing light levels. Consider the Static Spectrum Light Engine when the fixtures will illuminate spaces occupied primarily during the daytime hours.


DYNAMIC LIGHT ENGINE - Option Codes 30KD, 35KD, 40KD

BIOS SkyBlue Dynamic Spectrum lighting solutions provide full daytime circadian stimulus, communicating directly with human circadian biology through a non-visual photo receptor in the eye. With SkyBlue, there is no need for color tuning, color temperature adjustments, or extra illumination. The SkyBlue Dynamic Light Engine automatically calibrates the light level, reducing melanopic lux while keeping photopic lux at a constant level when used in conjunction with proper dimming controls. Consider the Dynamic Spectrum Light Engine when the fixtures will illuminate spaces occupied during both daytime and nighttime hours.


FIXTURE LENGTHS	
LENGTH CODE	LENGTH - WFL, WT
2'	22.50"
3'	33.50"
4'	44.50"
5'	55.75"
6'	66.75"
7'	78.00"
8'	89.00"

NOMINAL LUMENS AT 4000K - 80CRI

2700 (90CRI)	89.1%
3000 (80CRI)	95.9%
3000 (90CRI)	92.3%
3500 (80CRI)	99.1%
3500 (90CRI)	95.0%
4000 (80CRI)	100%
4000 (90CRI)	95.9%
5000 (80CRI)	100.1%



**WALL MOUNT -
ADA COMPLIANT**



SUSPENDED