York - 24"

AIW11726 24 in



JOB NAME:

TYPE:

NOTES:

DESCRIPTION

The York is a simple but elegant sconce that can either be used as a decorative element or be painted to disappear in the space. The fixture can be designed for any application where elegance is important. Choose from a palette of both painted and metal finishes.

FEATURES & BENEFITS

- Compliant with Americans with Disabilities Act (ADA) requirements
- Versatile design allows fixture to be mounted in any orientation
- · Handcrafted in USA

SPECIFICATIONS


- LIGHT SOURCE: White LED light engine
- CRI: 80+ (contact factory for 90+)
- LUMEN MAINTENANCE: L70 = >50,000 Hrs.
- **CCT**: 3000K, 3500K, or 4000K
- DRIVER: Integral Class 2 power supply standard
- **DIMMING:** 0-10V controls standard to 1% on LED light engines
- EMERGENCY: Emergency battery remote optional
- LENS: Top lens and bottom lens standard with any LED module.
- **CONSTRUCTION:** Formed metal construction provides durable protection for internal components and is recyclable
- MOUNTING: Mounts to standard 4" octagonal junction box
- MODIFICATIONS: Consult factory for all modification requests
- APPROVALS: ETL listed to UL standards (US & Canada) for use in damp locations; not recommended for exterior applications





EMR

DIMENSIONS



٧	H 6 in 15.2 cm	D
.4 in	6 in	4 in
1 cm	15.2 cm	10.2 cm
Nounting \	Neight	
nproxima	te: 25 lb (12	ka)

CONFIGURATOR -

To configure your spec sheet online, go to www.spilighting.com/AlW11726. Not all options are available in all configurations; consult factory for details.

Required Field *



A - LIGHT SOURCE *

To ensure color consistency, SPI uses precise bin selection and strict quality processes to maintain a 3-step (MacAdam) SDCM on all white LED lampings. Published LED luminaire wattages are calculated using a typical power supply efficiency of 88%; exact wattages may vary based on application. Alternative wattages available upon request.

L11W | White 11W LED Light Engine | Delivered Lumens: 764

L22W | White 22W LED Light Engine | Delivered Lumens: 1,528

See last page for finish options

B-VOLTAGE*

120-277V | Universal Voltage

C-LAMP OPTIONS*

Delivered lumens shown are at 4000K CCT; apply multiplier for delivered lumens at other CCT.

■ 3000K ¹ | 3000K CCT

☐ **3500K** ² | 3500K CCT

4000K | 4000K CCT




¹ Apply .95 multiplier for delivered lumens

² Apply .97 multiplier for delivered lumens

D - FACEPLATE OPTIONS

Patterned stainless steel faceplates cannot be painted or metal finished. Please leave the primary finish BLANK when specifying this option.

- **ES1** | Embossed Stainless Steel-Linear Pattern
- **ES2** | Embossed Stainless Steel-Cross Hatch Pattern





Available Finishes

Not all finishes are available in all configurations; consult factory for details.

Brushed Aluminum

BAL	
Brushed Aluminum	

Brushed Brass

BBR	
Brushed Solid Brass	

Brushed Copper

BCU	
Brushed Solid Copper	

Paint Colors

PT01	PT02	PT03	PT04	PT05 Putty (Textured)
Super White (Gloss)	White (Textured)	Morning Light (Textured)	Warm White (Textured)	
PT06	PT07	PT08	PT09	PT10
Warm Beige (Textured)	Light Taupe (Textured)	Medium Taupe (Textured)	Medium Grey (Textured)	Dark Grey (Textured)
PT11	PT12	PT13	PT14	PT15
Black (Textured)	Dark Chocolate (Textured)	Warm Grey (Textured)	Light Grey (Textured)	Sage (Textured)
PT16	PT17	PT18 Deep Red (Textured)	PT19	PT20
Spruce (Textured)	Red (Textured)		Blue (Textured)	Dark Green (Textured)
PT21 Pearl White (Metallic Gloss)	PT22 Platinum (Metallic Gloss)	PT27 Deep Copper (Metallic Gloss)	PT28 Dark Stainless (Metallic Gloss)	PT29 Red Brass (Metallic Gloss)
PT31 Medium Bronze (Metallic Gloss)	PT32 Dark Bronze (Metallic Gloss)	PT33 Dark Blue (Textured)	PT40 Yellow (Textured)	PT41 Orange (Textured)
PT42	PT43	PT44	PT45	PT46 Aluminum (Metallic Textured)
Sky Blue (Textured)	Teal (Textured)	Green (Textured)	Purple (Textured)	
PT47 Deep Red Brass (Metallic Textured)	PT48 Brass (Metallic Textured)	PT49 Bronze (Metallic Textured)	PT51 Matte White (Textured)	

